

High Density Polyethylene



HF09522

EVALENE® HF09522 is a high molecular weight High Density Polyethylene grade for blown film applications.

EVALENE® HF09522 is ideal for stiff and strong films. Bags made of **EVALENE® HF09522** can carry heavy loads and exhibit good puncture resistance. Packaging made from **EVALENE® HF09522** has superior performance and good barrier resistance against moisture and oxygen. Downgauging using **EVALENE® HF09522** is highly recommended due to its superior mechanical properties. Optimum gauge reduction is a real possibility.

FEATURES

- Superior toughness
- High stiffness
- Good puncture resistance
- Good moisture barrier properties
- Meets FDA Philippines food-contact requirements
- Halal certified

TYPICAL APPLICATIONS

- Grocery bags
- Supermarket produce bags
- Carrier bags
- Trash bags
- Sack liners

Product Properties

Property	Test Condition	Test Method	Typical Value	Unit
Flow Index ¹	190°C/21.6 kg	ASTM D1238	9	g/10 min
Melt Index	190°C/2.16 kg	ASTM D1238	0.075	g/10 min
Density	23°C	ASTM D1505	0.952	g/cm ³
Tensile Strength at Yield*	500 mm/min	ASTM D882	27 / 28	MPa
Elongation at Yield*	500 mm/min	ASTM D882	9 / 5	%
Tensile Strength at Break*	500 mm/min	ASTM D882	37 / 22	MPa
Elongation at Break*	500 mm/min	ASTM D882	226 / 332	%
Tensile Modulus*	1% Secant, 25 mm/min	ASTM D882	786 / 940	MPa
Elmendorf Tear Strength*		ASTM D1922	21 / 336	g
Dart Drop Impact Strength*		ASTM D1709	160	g

¹Product is controlled by Flow Index. Melt Index is estimated for customer use.


*Properties tested on 25µ films as extruded on 60 mm die, 3.2:1 BUR, at 12 - 17 m/min take-up speed.

Tensile and tear properties are in machine and transverse directions (MD / TD).

Typical Processing Conditions

Extrusion Temperatures	180 - 230°C
Blow Up Ratio	3 - 5
Die Gap	0.8 - 1.3 mm

Figure 1. Mechanical property performance of
EVALENE® HF09522 vs. other HDPE material



EVALENE® HF09522 delivers benefits to the converter and the end-user alike. Its overall superior mechanical properties over the other HDPE material is evident in this side-by-side comparison. **EVALENE® HF09522** likewise exhibits outstanding stiffness-toughness balance which makes it suitable for a wide range of applications. Finally, **EVALENE® HF09522** has at least 10% advantage on tensile strength over the other HDPE material, opening up opportunities to downgauge. Because of this superior tensile strength, higher load-bearing capacity can be expected from a bag made of **EVALENE® HF09522** which is a major advantage for a grocery, shopping or any other carrier bag.

Disclaimer:

Information provided herein is given for general purposes only. It is the customer's sole responsibility to test the product and any information provided herein to determine whether they are suitable for the customer's purposes. JGSPC MAKES NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OF ANY OTHER NATURE ARE MADE HEREUNDER WITH RESPECT TO INFORMATION OR THE PRODUCT TO WHICH INFORMATION REFERS. Customers are strongly advised to review the applicable Material Safety Data Sheet before handling or using the product described herein.



Find out more about us at:
www.jgspetrochem.com